


short radius elbow



SHORT RADIUS ELBOWS

TRIMMED AT TANGENT




DESIGNED FOR SYSTEMS WHICH REQUIRE TIGHT RADIUS BENDS. AVAILABLE IN 8 POPULAR SIZES 3 INCH TO 6 INCH ARE 16 GA. 7 INCH IS 14 GA. 8 AND 10 INCH ARE 12 GA.

MILL	CHROME	OD	RAD	C/END	BEND DEG.
IT 3-300	IT 403-300	3"	3"	3"	90
IT 3-350	IT 403-350	3-1/2"	3-1/2"	3-1/2"	90
IT 3-400	IT 403-400	4"	4"	4"	90
IT 3-500	IT 403-500	5"	5-1/2"	5-1/2"	90
IT 3-600	IT 403-600	6"	6"	6"	90
IT 3-700	IT 403-700	7"	9"	9"	90
IT 3-745	IT 403-745	7"	9"	3-3/4"	45
IT 3-800	IT 403-800	8"	9-7/8"	9-7/8"	90
IT 3-845	IT 403-845	8"	9-7/8"	4-3/32"	45
IT 3-1090	IT 403-1090	10"	11"	11"	90
IT 3-1045	IT 403-1045	10"	11"	4-9/16"	45

SPECIAL SHORT RADIUS 90 DEGREE ELBOWS


PLAIN END



PARTS COME WITH PLAIN ENDS FOR DIRECT ATTACHEMNT INTO FLEX HOSE OR FOR INSTALLATION INTO A MUFFLER. ALL ARE 16 GA.

MILL	CHROME	OD	RAD	C/END
IT 4-202	IT 404-202	2"	2"	4"
IT 4-252	IT 404-252	2-1/2"	2-1/2"	5"
IT 4-302	IT 404-302	3"	3"	5"
IT 4-352	IT 404-352	3-1/2"	3-1/2"	5-1/2"
IT 4-402	IT 404-402	4"	4"	6"
IT 4-446	IT 404-446	4"	4"	10",8"
IT 4-503	IT 404-503	5"	5-1/2"	7-1/2"
IT 4-509	IT 404-509	5"	5-1/2"	10"
IT 4-515	IT 404-515	5"	5-1/2"	15"
IT 4-548	IT 404-548	5"	5-1/2"	13-1/2",9-1/2"
IT 4-548M	IT 404-548M	5"	5-1/2"	19-1/2",10-1/2"
IT 4-604	IT 404-604	6"	6"	10"

EXPANDED AND SLOTTED



ALL ELBOWS EXCEPT 3 SERIES SHOWN IN TOP SKETCH MAY BE EXPANDED AND SLOTTED AT EXTRA COST. USE "ES" WHEN ORDERING

IT 4-202ES	IT 404-202ES	2"	2"	4"
IT 4-252ES	IT 404-252ES	2-1/2"	2-1/2"	5"
IT 4-302ES	IT 404-302ES	3"	3"	5"
IT 4-352ES	IT 404-352ES	3-1/2"	3-1/2"	5-1/2"
IT 4-402ES	IT 404-402ES	4"	4"	6"
IT 4-446ES	IT 404-446ES	4"	4"	10",8"
IT 4-503ES	IT 404-503ES	5"	5-1/2"	7-1/2"
IT 4-509ES	IT 404-509ES	5"	5-1/2"	10"
IT 4-515ES	IT 404-515ES	5"	5-1/2"	15"
IT 4-548ES	IT 404-548ES	5"	5-1/2"	13-1/2",9-1/2"
IT 4-548M-ES	IT 404-548M-ES	5"	5-1/2"	19-1/2",10-1/2"
IT 4-604ES	IT 404-604ES	6"	6"	10"